

RFS-700D

Compact Rubidium Frequency Standard



Brandywine's RFS-700D is a miniaturized Rubidium Frequency Reference in a compact ruggedized package designed for mounting on a DIN rail system. The RFS-700D is capable of outputting 7x 10MHz frequency reference with low phase noise.

The frequency standard includes a low phase noise oven controlled quartz oscillator, which is frequency locked to the rubidium oscillator. The time constant of this loop is selected such that the short term stability (and phase noise) of the outputs are determined by the OCXO characteristics, which the long term stability is determined from the rubidium oscillator.

The frequency standard has internal temperature sensors that are used to compensate the oscillator, based on a factory calibration, to improve the overall accuracy of the system.

The unit has been designed to meet the requirements for MIL-STD-810F for operation in demanding environments.

Specifications

Output Specifications

Connector type:	SMA
No. of connectors:	7
Output Frequency:	10 MHz
Output impedance:	50Ω
Short term stability:	1 E-11
Aging:	5 E-11 per Month
Phase Noise @ 100Hz	-138 dBc/Hz
Phase Noise @ 1kHz	-151 dBc/Hz
Phase Noise @10kHz	-165 dBc/Hz
Phase Noise @100kHz	-165 dBc/Hz

Ethernet

Port speed:	10/100BaseT
Protocols supported:	SNMPv3
Fault reporting:	Output fail (1-7), Rb Lock Status, PLL lock status, Over current, (OCXO)temp.

Power

Input Voltage Range:	18-28 VDC
Nominal Input Voltage:	24 VDC
Input Connector:	Terminal Block
Power consumption:	15 W

Environmental

Operating temp.:	-30 deg. C to +65 deg. C
Storage temp.:	-40 deg. C to +85 deg. C
Humidity:	95% Non-condensing
Operating Altitude:	10,000 ft. ASL
Non-Operating Altitude:	50,000 ft. ASL