

XMC-SyncClock32

- IRIG A & B, NASA 36 and 1 PPS inputs standard
- HaveQuick sync option
- Propagation delay compensation
- Zero latency time reads
- Match Time output
- IRIG B time code output
- External Event time tags
- *On-board* GPS receiver option
- User programmable heartbeat rate



The XMC-SyncClock32 from Brandywine Communications is an advanced switched Mezzanine Card (XMC) module. Precision time is provided to the host computer with zero latency. The on-board microprocessor automatically synchronizes the clock to reference signal inputs. The reference signal inputs handled by the XMC in its standard configuration are IRIG's A and B, NASA 36 and 1 PPS. Alternatively, the clock in the XMC can be set using commands from host computer and free run using its on-board oscillator as the time base.

When synchronizing to time codes or 1 PPS the microprocessor constantly measures the time error between the on-board clock and the reference input code and adjusts the error measurement for propagation delay. When the disciplined TCXO option is selected the residual error is used in an adaptive gain loop to adjust the frequency of the 10 MHz oscillator for minimum error. Before being used as the time reference, the input code reference is checked (to code carrier resolution) for consistency with itself. If the incoming code is missing or corrupted by noise the on-board clock is updated by the 10 MHz oscillator. When the input code is again useable the correction loop is smoothly closed.

58 bits of BCD time are available to the host computer using two zero latency time reads. The time message contains units of microseconds through units of years. A status word is available using an additional read.

The time-of-occurrence of external events may be captured (time-tagged) by using the Event Time input. When the event input is sensed the current time is saved in a buffer for later interrogation by the host. The resolution of the time tag is 100 nanoseconds.

The Match Time feature may be used to automatically initiate or terminate an external process. The resolution of the Match Time comparison is one microsecond. The Match Time output is asserted when the time of the internal clock matches that of the user input start time. The Match Time output may be terminated by a user command or when the previously set stop time is encountered.

One user programmable heartbeat rate is provided. The heartbeat pulse rate provides heartbeat timing to the host computer and is also available on the multi-pin connector.

The GPS synchronization option offers worldwide time transfer capability to the XMC-SyncClock32. Very precise synchronization, automatic leap year and leap second correction, plus accurate position information are additional benefits provided by the GPS option.

brandywine communications

XMC-SyncClock32 Specifications

General Input Specifications

Input Codes	IRIG A & B, NASA 36
Input Amplitude	.25 to 10 Vpp
Input Impedance	>10k Ohms
Ratio	2:1 to 4:1
Frequency Error	100 PPM maximum
Code Sync Accuracy	One microsecond
1 PPS input	RS-422 or TTL, positive edge
1 PPS Sync Accuracy	300 nanoseconds
External Event	
Resolution	100 nanoseconds–units year
Min. event spacing	None

General Output Specifications

IRIG B DC Shift	TTL
Match Pulse	TTL level at Start–Stop time
Resolution	Microseconds–eight millisecond
Heartbeat Rate	Interrupt, flag, TTL, negative going
Clock Divisor	2–65,535
Clock Input	1 MPPS
Default output	1 kPPS
BCD Time	Microseconds–unit year on demand, zero latency 58 bits in two 32 bit words
Status word	8 bits
Status LED	Flashes coded patterns
Interrupts	External Event, RAM FIFO, Heartbeat, Match Time
Flags	Dual Port RAM data ready, FIFO data ready, In sync, Heartbeat, Match Time, External Event
Connectors	SMB, high density IEEE–1284
MTBF	141,000 hours per Mil-217-F, Notice 2, 25° C, ground benign

Mechanical & Environmental

Size	74mm X 1437.5mm single CMC
Type	PCIe endpoint
Power	
+ 5 Vdc	±5%, 150 mA maximum
+12 Vdc	±5%, 60 mA maximum
-12 Vdc	±5%, 25 mA maximum
Operating Temperature	0°C to +70°C
Storage Temperature	-40°C to +85°C
Humidity	To 95% without condensation

Options

GPS Sync Input (external)	C/A code
Sync Accuracy	100 nanoseconds
Position Accuracy	25 meters SEP
Tracking	Twelve parallel channels
Antenna*	L1, 25' cable
Antenna Options	
Hi-gain	L1, mast mount, 100' cable
Input Code Isolation	Transformer coupling
Input Codes	IRIG G, XR3, 2137, IRIG E, 109-60
Output Codes (DSL S)	IRIG A, NASA 36, IRIG G
Eight External Event Inputs	TTL, positive or negative edge
Have Quick Input	Per ICD–GPS–060
Have Quick Output	Per ICD–GPS–060
Binary Time Words	Replaces BCD
Oscillator Upgrades	Disciplined TCXO, 1 PPM
1 PPS 10 Vdc input	Sync input, +10 Vdc, 50 Ohms

*consult factory for cable length options

Other **brandywine communications** products

Video Character Inserters

Time-Message Displays

VME, PMC, PC/104, PCI, CPCI, PCIe Computer Clock

Synchronization Boards

Network Time Servers

Frequency Generation and Distribution Instruments

Dual & Triple Redundant Systems

Rev. A 06/01/2018
© Brandywine Communications 2018